
In accordance with its program in the field of medicinal and biochemical research the Institute had to expand its premises at Naggar and early in 1933 commenced the building of a biochemical laboratory, where this research is to be conducted. The new building, with the exception of its inner technical installation and equipment, was completed by the end of the same autumn. The construction was made possible thanks to a donation of a friend of the Institute in New-York, who desires to remain anonymous.

For the benefit of those who know little of North-Western India, it has be mentioned that the Beas Valley, in which Naggar is situated, lies in the western part of the Great Himalayan Range, the glaciers of which surround the upper Beas from three sides (N, E & W within ten miles by airline) the nearest highest peaks of these glaciers being 21,760 and 23,050 ft above sea level, straight to the East from Naggar, 33 and 65 miles respectively by airline. The range on the slope of which Naggar is situated, has peaks 13,500 to 14,500 ft high (what is higher than Mt.Jungfrau in the Bernese Alps), with a pass - Chandarkhani P. - 12,200 ft leading into the Malana Valley. This pass is less than six miles by road from Naggar. Despite the high altitudes, vegetation grows up to 19,000 ft in the summer, which is higher three thousand feet mare than the Montbland The Latitude of Mulu is that of Marocco. The following table gives the mean temperatures in C^o and F^o of Naggar for each month, as compared with the most extreme and normal temperatures of the world;

X "Programme" unlers American epetting is desired



more

To the North of Kulu lies Lahul, to the West Chamba State, to the East - Spiti and to the South Mandi State and Bashahr.

The actual height of the Laboratory building above sea level is 6,220 ft The building lies to the East of the Institute's Headquarters and is separated from these headquarters by a passage four yards wide, both the building running in one straight frontage line. The foundation is laid on solid rock and is 64 ft by 51 ft; the total floor space of the ground and upper floors is 4076 squ.ft and the total wallspace 10,523 squ.ft. The height of the ground floor rooms is the ft and of the upper storey rooms 9'3".

The general layout of the laboratory has been made according to suggestions of a biochemical expert with excellent practical research experience in this matter, with the intention in mind that present and future investigations of the phenomena of life should be largely based upon the interrelation of the various sciences, rather than on a narrow study of one only.

Each separate room has thus been planned for a certain type of research.

The older idea of arranging in a laboratory several rooms, in which every scientist research warker works by himself, has been abandoned. In the present layout the investigator can move from one laboratory into another, as his work requires, thus making it possible to provide every laboratory room with better and more specialized equipment, without duplicating the apparati in several rooms, and thus considerably improving the quality of research.

As to the building itself, there are 9 rooms on the ground floor, situated along a central corridor. As one enters the building, there is to the left the Organic & Pharmacological Laboratory 15 by 24 ft large, then the entrance to the Library and Study, each 12 by 14 ft, then the Photometric darkroom, 15 by 9 ft and the Physical Laboratory 23 by 21 ft. A cold room 16 by 9 ft, is at the further end of the corridor, on the coolest (eastern) side of the building, facing the rocks. This cold room will have double walls, ceiling and floor, leaving an air camera about 2" wide inbetween,

(air being the best isolator) and will be cooled by an electric refrigerating plant. A thermostat will regulate the temperature to be kept permanently at 5°C, which is the best for this kind of work.

To the right of the corridor are two rooms for Cancer Research, each 15 by 18 ft and the spaceous General Laboratory 32 by 18 ft large.

The laboratories will be heated by thermostatically controlled electric radiators, one under every window, automatically preventing the temperature from falling below the required point. The ideal temperature for such laboratories is 20°C (68°F), with variations from 15°C to 25°C being tolerable but higher temperatures being exceedingly objectionable, as no work involving biological material could then be carried out accurately. The refrigerating plant in its essentials consists of an electric motor driving a pump, a cooling liquid and a system of piping. This refrigerating liquid may be carried a considerable distance, thus providing refrigeration for all those rooms of the laboratory where a regulation of temperature is essential.

The ventilation of the rooms will be carried out by exhaust fans, probably the De Botezat type will be used and separate exhaust fans will have to be used for the hoods, preventing obnoxious gases in certain chemical work from finding their way into the rooms.

As we succeeded in obtaining from Joggindarnaggar twenty and twentyfour ferent iron girders, and thus could considerably strengthen the ceilings, somewhat the erection of the upper storey became possible, and six more partly spaceous rooms could be added to the building. This upper floor

is connected by a wooden staircase with the ground floor corridor, and
the rooms are 20' by 13', 15' by 12', 11' by 12', 10' by 13', 8' by 13'
one of
leads
and 8' by 12' large. A glass corridor from the NK upper rooms to a bridge,
which having a span of about 20 ft takes one onto the rocks to the East.

All rooms have extremely large windows, admitting the maximum possible amount of light from the outside. The ground floor windows are seven feet wide and five feet high, having nine glass panes 16" by 20", three thus admitting twenty squ. feet of outside light. The large General, Physical and Organic laboratories have each two such windows. The indoor lighting will be electric.

The construction is in wood and stone, covered with plaster and whitewashed. This method of construction is known here as the dhajji diwar construction and has proved to be the best, if not even the only, method of construction that resists earthquakes, which used to be quite frequent in this region. Most of the Government buildings in Wharmsala for instace, are built in this style and have proved to be the best. It is interesting that in its essential principle this mode of building rather resembles the steel structure of modern skyscrapers, with the diffierence of course that wooden beams are used instead of steel girders. Thus the wisdom of the people in its own way arrived to its best solution, how to give utmost binding strength and rigidity on hand of the local material available. The walls axexempwaxexxxx attached photographs, showing how the vertical beams are bound by horizontal bams, and the resulting squares are fortified with a diagonal cross, making the skeleton structure perfectly stress and strain resisting on the same principle as the triangular girder construction. All corners and joints are then strengthened by steel bolts and iron hooks and the open triangular spaces are the filled with large and binding material, and the walls plastered inside and outside and whitewashed. This actually makes the whole wall become one solid piece.

Over a hundred trees were required for the wooden part of the 2 construction and for seasoning timber for furniture making for the laboratory. Since the Forest Department was not in a position to sell us trees nearer than mixed unselected forest plots at Devi-di-Jhir and Patha-Nali (beyond and above Bundrols), a distance of eleven miles and on the opposite side of the Beas River, we express our thanks to Mr.W.H.Donald for selling to the Institute trees at our own selection from his forests at made by Ghordrour and Kalaunti. The carriage was arranged on coolies. Most of the trees were blue pine (local name "kail", Pinus excelsa), but for windows, and doors and furniture, deodar wood (local name "kelo", Cedrus Libani Deodara) was used. Ceiling and floors, whereever the latter ware not

x kad already been purchased laid in large stone, slabs, were made in spruce (local name "rai". Picea The timberXwas purchased already in 1931 and had been stocked to season. Morinda). Stone was available from near by rocks and about twenty two thousand cubic feet were used. The large square stone slabs (four square feet each) for flooring are also to man be had nearby and a about half for a thousand of these were required. The roofing took over 350 corrugated oron sheets to be completed, which together with other Euferial, like on lorries bolts, screws, instruments, etc had to be brought, from Amritsar and Lahore, a distance of 300 miles from Naggar.

The maximum number of workmen employed at a time was 72. The the head carpenters were from Hosniarpur, and the rest of carpenters, masons, coolies etc. were employed locally. Naturally every detail of construction, and planning, outlay, levelling, measuring had to be personally supervised directed and minutely supervised.

The clearing of the side for the laboratory necessitated further the removal of the old dilapidated servants quarters and kitchen, and new servants quarters 40 feet long by 13th ft wide, were constructed to the NE of the laboratory on a plot of land also donated by Prof.de Roerich

for this purpose. The servants' quarters have four rooms, 12 feet by nine and a half ft, with a window and door each. I veranda runs along the whole length of the quarters. A new kitchen has also been constructed, adjoining the Institute's Headquarter building.

It remains now to install the laboratory equipment and fixtures and to fit water supply and electric light and power. Thanks to the advantageous situation in the hills, it is possible to terive electric power from a near-by mountain stream, which can be conducted in a channel to give a hundred feet drop, thus providing for about eighty KW of electricity. A survey of the spot has already been made and found by experts to be fully suitable. Estimates for the hydro-electric plant are expected as well as the granting of the necessary land and water rights. The turbine and generator would be located on the Chhaki river, hardly four furlongs from the Institute's buildings and current will be transmitted by overhead lines. It is planned to install a 110 V. A.C. current, three phase, fifty cycles. The concumption of the electric room heaters, chemical heaters, thermostats, pressure pump, refrigerating plant and electric motor is estimated at 55 KW, the balance being required for lighting of all the buildings, motors for carpenters' workshop, stoves, fans, driers, etc. and for possible expansion in the future. A converter will be installed to change part of the current to D.C. Whilst it is impossible in this short article to dwell on the

biochemical side of the Laboratory work to be carried out (particulars of preliminary collections for which are mentioned elsewhere in this Journal, and particulars of the remember 1 boratory research work will follow in later issues of the Journal when the work will have been started), but it is interesting to mention here, that though considerable biochemical and botanical research work is being carried out in India by able scientists in the laboratories at Dehra Dun and at Calcutta, etc., our Institute is the first to establish such modern up-to-date labora-

on the spot under ideal conditions (with nurseries and plantations) on 1 i v i ng mount a in herbs and plants. Why the properties of medicinal plants growing on altitudes are different, is not in the competency of the writer to discuss here, but it would seem that already the very much lower pressure atmospheric pressur (for example on 15,000 ft (17,2") above sea level 427 mm as compared to 760 mm at sea level) and the different composition of the atmosphere must have a considerable influence on plant life, its cell structure, plant nutrition, etc.; and no doubt these are only two of numerous other influences and conditions.

The Secretary.